



Sample image

## KG127

Type Size: S2

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Bolt terminal/Screw terminal

### IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

**Rated insulation voltage Ui**

Voltage (V)	AC / DC
1000	AC

**Rated impulse withstand voltage Uimp**

Voltage (kV)	Overtoltage category	Pollution degree	Supply system	Function
8	III	3	Valid for lines with grounded common neutral termination	Switch / Switch disconnecter

**Rated uninterrupted current Iu/Ith**

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	additional requirements
125	50	55	Ambient temperature +50°C during 24 hours with peaks up to +55°C

**Conventional enclosed thermal current Ithe**

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	Additional requirements	No. of stages (from - to)	Mounting	Mounting size
125	35	40	Ambient temperature +35°C during 24 hours with peaks up to +40°C	--	--	--

**Rated operational current Ie**

Utilization category	Voltage (V)	Current (A)
AC-32A	20 - 400	125
AC-20A	1000	125
AC-21A	20 - 690	125
AC-22A	220 - 500	125
AC-22A	660 - 690	100

**Rated operational power**

Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-3	220 - 240	3	3	22
AC-3	380 - 440	3	3	37
AC-3	500 - 500	3	3	45
AC-3	660 - 690	3	3	30
AC-23A	220 - 240	3	3	30
AC-23A	380 - 440	3	3	45
AC-23A	500 - 500	3	3	55
AC-23A	660 - 690	3	3	37

**Max. Fuse rating IEC**

Fuse characteristic	No. of Fuses	Current (A)
gG	1	125

### UL60947-4-1, UL508

**Rated insulation voltage Ui**

Voltage (V)	AC / DC
600	AC

**Rated thermal current**

Current (A)	Ambient temperature (°C)	Additional Text
150	0 - 40	--

**General Information**
**Text**

- The operating handle and position indicating means to be used with these manual motor controllers should be provided from the manufacturer, or the operating handle and position indicating means to be used should have been previously evaluated in combination with the manual motor controllers.

### CSA

**Rated insulation voltage Ui**

Voltage (V)	AC / DC
600	AC

Rated thermal current			
	Current (A)	Ambient temperature (°C)	Additional Text
	150	0 - 40	-

**GENERAL TECHNICAL INFORMATION**

Tightening torque of screws	
	tightening torque (Nm)
	14

Rated short-time withstand current Icw	
	Time (s)
	1

Size of conductor				
composition of conductor	Min. / Max. value	No. of conductor per terminal	Cross section (mm <sup>2</sup> ) or (AWG/kcmil)	Material of the wire
Flexible wire	Max.	1	70mm <sup>2</sup>	Copper
Flexible wire	Max.	1	AWG 2/0	Copper
Single-core or stranded wire	Max.	1	95mm <sup>2</sup>	Copper
Single-core or stranded wire	Max.	1	AWG 3/0	Copper
Flexible wire with sleeve	Max.	1	70mm <sup>2</sup>	Copper

Approbations	
Specification	Marking

EAC



CE marking



UK Directives

IEC 60947-3; EN 60947-3; VDE 0660 Teil107

**IEC 60947-3  
EN 60947-3**

IEC 60947-6-1

**IEC 60947-6-1  
EN 60947-6-1**

UL 60947-4-1; CSA C22.2 No. 60947-4-1



CSA C.22.2 No.14



GB/T14048.3



Power loss per pole

Power (W)

3,10

Conditions during transport and storing

Minimum temperature (°C)

-40

Maximum temperature (°C)

85

additional requirements

In case of temperatures below -5°C no shock load permissible

General Information

Text

- The wiring aid has to be removed before voltage is applied!
- EMC Note: This device is suitable for use in environment A and B.
- Terminals with factory fitted jumper links are tightened during production for loss prevention. When opening the terminal clamps, make sure that no factory fitted links get lost and that all wire connections are properly seated.
- After wiring, ALL terminal screws must be tightened to the specified torque values.
- The protection class of the selected mounting type may vary if optional extras are used.
- Do not lubricate or treat contacts.
- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.

Operating temperature

Min. Temperature [°C]

-5

Max. Temperature [°C]

55

Dimensions ring cable lug

A(mm)	20,00 mm
A(mm)	25,00 mm